INTRUVENT

THREAT ACTOR INTELLIGENCE PROFILE

APT33

IRGC-Cloud Espionage and Destructive Operations Group | Peach Sandstorm | Refined Kitten

Group ID: APT33 | Classification: TA-Tracked | Last Updated: March 18, 2026 | Confidence: Moderate – Multi-source attribution | Report: 2026-APT33-V2

Intruvent Technologies | 447-591-4538 | 477-591-4538 | 477-591-4538

13+

Years of Continuous Cyber Espionage Operations Since 2013

Persian-nexus actor with IRGC-aligned tasking, targeting aerospace, energy, petrochemical, and defense sectors.

Attribution & Identity

ATTRIBUTION CONFIDENCE: HIGH

Multiple independent vendors and government agencies converge on Iranian origin. Infrastructure overlaps with APT34 and APT35 tooling. Operational tempo correlates with Iranian state interests including sanctions relief negotiations and regional conflict escalation.

Background

APT33 is an Iranian state-sponsored threat group that has conducted espionage and destructive operations since at least 2013. The group targets organizations in the aerospace, energy, petrochemical, and defense sectors, with a primary focus on entities in the United States, South Korea, and Saudi Arabia. The United States Department of Justice has publicly attributed the group to Iran's Islamic Revolutionary Guard Corps (IRGC), specifically to the Iranian Cyber Electronic Command (CEC). APT33 is also tracked under the names Peach Sandstorm (Microsoft), Refined Kitten (CrowdStrike), and Holmium (Microsoft). Several publicly reported campaigns have overlapped with those conducted by APT34 and APT35, suggesting shared infrastructure, tooling, or operational coordination among these Iranian actors.

Known Aliases

Peach Sandstorm | Refined Kitten | Holmium | Magnallium | Elfin | Curious Serpens | Cobalt Dickens | Cobalt Trinity | Cobalt Ulster | Cobalt Mirage | Cobalt Gypsy Rain | Cobalt Hatchman | Cobalt Wilson | Cobalt Wilson | Cobalt Wilson

Quick Facts

- Origin: Iran (IRGC)
- Active Since: 2013 earliest confirmed activity
- Motivation: Espionage, destruction, financial
- Sponsor: IRGC-Quds Force
- Last Observed: Jan 2026 (Microsoft)
- Exploitation Vector: Spear-phishing, Custom backdoors
- Custom Tools: Shamoon, TurnedUp, Stonedrill, Tickler
- OPSEC Level: Moderate
- Aggressive Operations: Shamoon wiper attacks (2012, 2016, 2018)
- Infrastructure Overlap: APT34, APT35
- Sanctioned: Yes (US, EU, UK)
- ATT&CK Groups: G0064

Threat Intelligence Operational Posture

APT33 has shown persistent interest in organizations in the aviation sector involved in both military and commercial capabilities. As well as organizations in the energy sector with ties to petrochemical production.

Victoria Marchetti, SITU Inc. Nick Hawkins, Air Force Cyber Operations Group* December 2017

Targeting Profile

Industries
- Energy (Petrochemical primary, since 2013)
- Aviation (Aerospace primary, since 2013)
- Defense-Industrial Base (DIB) (secondary)
- Satellite / Space (Commercial contractors)
- Government (local and state, limited)
- Communications Equipment (Cisco, 2018)
- Oil and Gas (Trisis, 2019)
- Digital Identities (Infrastructure and security)
- Manufacturing (ICS/Lessened)

Regions
- Saudi Arabia (primary, strategic)
- United States (defense, government, energy)
- South Korea (energy, petrochemical)
- Israel (defense, government)
- United Arab Emirates (secondary)
- Australia (education, defense, energy)

Technologies Targeted
- Azure AD / Entra ID (password spraying)
- Microsoft 365 (cloud-based mailbox theft)
- Azure Subscriptions (VM compromise)
- Exchange Web Access (email exfiltration)
- VPN Gateways (initial access)
- Windows Credentials (Kerberoasting)
- Active Directory (AD) (reconnaissance, Kerberoasting)

Tactics, Techniques & Procedures

The following MITRE ATT&CK techniques are documented for APT33 (G0064) from the Intruvent Cluster (T1 Campaign), MITRE ATT&CK, and Intruvent Threat Intelligence.

INITIAL ACCESS
- T1566.001 Spearphishing Attachment
- T1566.002 Spearphishing Link
- T1091 Hardcoded
- T1078.004 Cloud Accounts NEW

EXECUTION
- T1059.001 PowerShell
- T1059.003 Windows Command Shell
- T1204.002 Malicious File
- T1047 Windows Management Instrumentation

PERSISTENCE
- T1053.005 Scheduled Task
- T1547.001 Registry Run Keys / Startup Folder
- T1546.003 Windows Management Instrumentation Event Subscription

PRIVILEGE ESCALATION
- T1134.001 Token Impersonation / Theft NEW
- T1078.004 Cloud Accounts NEW
- T1484.001 Group Policy Modification
- T1055.012 Process Hollowing
- T1068 Exploitation for Local Privilege Escalation

DEFENSE EVASION
- T1070.004 File Deletion
- T1027 Obfuscated Files or Information
- T1140 Deobfuscate/Decode Files or Information
- T1036.005 Masquerading: Match Legitimate Name or Location
- T1562.001 Disable or Modify Tools
- T1218.011 Signed Binary Proxy Execution: Rundll32

CREDENTIAL ACCESS
- T1110.003 Password Spraying NEW
- T1003.001 LSASS Memory
- T1558.003 Kerberoasting
- T1552.001 Credentials In Files
- T1555.003 Credentials from Password Stores
- T1056.001 Keylogging

DISCOVERY
- T1087 Account Discovery
- T1018 Remote System Discovery
- T1046 Network Service Scanning
- T1082 System Information Discovery
- T1083 File and Directory Discovery
- T1135 Network Share Discovery
- T1069.002 Permission Groups Discovery: Domain Groups
- T1482 Domain Trust Discovery

LATERAL MOVEMENT
- T1021.001 Remote Desktop Protocol
- T1021.002 SMB/Windows Admin Shares
- T1021.006 Windows Remote Management
- T1550.002 Pass the Hash
- T1570 Lateral Tool Transfer

COLLECTION & DATA STAGING
- T1560.001 Archive Collected Data: Archive via Utility
- T1005 Data from Local System
- T1039 Data from Network Shared Drive
- T1114.002 Remote Email Collection

COMMAND AND CONTROL
- T1071.001 Application Layer Protocol: Web Protocols
- T1573.001 Encrypted Channel: Symmetric Cryptography
- T1105 Ingress Tool Transfer
- T1090.003 Proxy: Multi-hop Proxy
- T1572 Protocol Tunneling
- T1219 Remote Access Software

IMPACT
- T1486 Data Encrypted for Impact
- T1490 Inhibit System Recovery
- T1561.002 Disk Wipe: Disk Structure Wipe

Operational Evolution: From Spearphishing to Cloud Abuse

Intruvent's analysis of APT33 activity from 2019 to 2026 reveals a significant shift in initial access methodology. Whereas in 2019, the group relied heavily on spearphishing with malicious attachments (T1566.001) and hardcoded credentials (T1091), by 2024 it had transitioned to password spraying against cloud identity providers (T1110.003) and abuse of cloud accounts (T1078.004). This evolution mirrors broader trends in Iranian cyber operations, as documented by Microsoft Threat Intelligence and CISA advisories.

Tooling & Infrastructure

Custom/Malware Arsenal

Tool	Description	First Seen
TURNEDUP (Backdoor)	Backdoor variant. Has an unknown purpose but has custom communication protocol. Uses a hard-coded 4-byte XOR key. Delivered as a dropped PE file. Variant: Intruvent-TURNEDUP-2019.	2019
DROPSHOT (Dropper)	Dropper that delivers TURNEDUP and SHAMOON. Observed in Saudi Aramid-like attacks. Uses a service for persistence. Suspected to drop a wiper.	2016
SHAMOON (Wiper)	Disk-wiping tool. Overwrites MBR and partition tables. Uses a kernel driver (RawDisk) to bypass user-mode protections. Destructive payload.	2012
TURNEDTOOL (Backdoor)	Backdoor variant. Uses HTTP for C2. Has a unique beacon format. Suspected to be a successor to TURNEDUP.	2017
Trutus (Backdoor)	Custom post-exploitation framework. Observed in 2019 campaigns. Has modules for credential dumping, lateral movement, and persistence. Uses a custom C2 protocol.	2019
Tickler (Backdoor)	Custom backdoor. Has a unique beacon format. Suspected to be a successor to TURNEDUP. Uses a custom C2 protocol. Has modules for credential dumping, lateral movement, and persistence.	May 2023
Stonedrill (Backdoor)	Backdoor variant. Has a unique beacon format. Suspected to be a successor to TURNEDUP. Uses a custom C2 protocol. Has modules for credential dumping, lateral movement, and persistence.	2019

Open-Source and Dual-Use Tools

Tool	Purpose	Source
Mimikatz	Credential dumping (LSASS memory, Kerberos tickets)	MITRE S0002
LaZagne	Credential dumping (browsers, databases, email clients, databases)	MITRE S0349
Rubeus	Kerberoasting/Golden ticket for persistence and command execution via kerb ops	MITRE S0363
Impacket	Collection of Python tools for network protocols (SMB, RDP, WMI, etc.)	MITRE S0357
PsExec	Lateral movement via service creation	MITRE S0029
Cobalt Strike	Commercial C2 framework (used in some campaigns, not primary)	MITRE S0154
Plink	Command-line PuTTY interface for scripting (used for tunnel creation)	MITRE S0279
Nmap (NSE)	Cross-platform NSE port scanner for network service discovery	MITRE S0589
BeaconEye (NSE)	Community NSE used to scan for Cobalt Strike beacon configurations	MITRE S0154
NETWMI (NSE)	Community NSE used to execute WMI queries remotely	MITRE S0358
Sysinternals Suite (NSE)	Suite of tools used for system administration and troubleshooting	Microsoft (2006)
Sysmon (NSE)	Windows system service and device driver that monitors and logs system activity	Microsoft (2014)
Windows Event Forwarding (NSE)	Native Windows feature used to forward and collect event logs	Microsoft (2005)
Windows Management Instrumentation (NSE)	Infrastructure for management data and operations	Microsoft (2000)

Infrastructure

Category	Details	Status
Hosting	Frequently uses compromised small business and personal websites, often in Eastern Europe, Malaysia, and the United States, as well as Taiwan. C2 infrastructure rotates every 2–4 weeks.	Ongoing (2013–present)
Domain Registration	Registers domains using fake identities from Belarus, Romania, and Russia. Typically registers 5–10 domains per month.	Ongoing (2013–present)
Bulletproof Hosting	Uses bulletproof hosting providers in Russia and Ukraine for some campaigns.	Ongoing (2013–present)
Cloud Infrastructure	Leverages cloud infrastructure (AWS, Azure, DigitalOcean) for staging and exfiltration.	Ongoing (2013–present)

Notable Campaigns

Aviation and Energy Sector Espionage

Sept 2019 – Present | United States | Saudi Arabia | Energy | Aviation

Intruvent's first observed campaign targeting aviation and energy sectors across the U.S. and Saudi Arabia. Spearphishing emails with malicious attachments (T1566.001) delivered TURNEDUP backdoor. Operators used PowerShell (T1059.001) and WMI (T1047) for execution. Credential dumping via Mimikatz (T1003.001) and LaZagne (T1555.003) enabled lateral movement via RDP (T1021.001) and SMB (T1021.002). Data staged in encrypted archives (T1560.001) and exfiltrated over HTTPS (T1071.001).

Attribution Note

The TTPs in this campaign (PDF-based spearphishing, use of custom tools) align with those used by Iranian-linked APT34 and APT35. Some researchers believe the APT33 activity may be a rebrand or a new name for APT34. Intruvent has not yet confirmed this relationship.

Shamoon 2.0 Destructive Campaign

Nov 2016 – Dec 2016 | Saudi Arabia | Energy | Destructive

Suspected Iranian-linked APT33 actor deployed a new variant of the Shamoon wiper malware. The attack targeted a single Saudi Arabian energy organization. Initial access was likely via spearphishing or exploitation of a public-facing application. The malware overwrote the Master Boot Record (MBR) and partition tables, rendering affected systems unbootable. Shamoon 2.0 included a new kernel driver (RawDisk) to bypass user-mode protections. Recovery required full system rebuilds. Intruvent assessed the use of Shamoon 2.0 as a destructive operation, likely intended to disrupt operations rather than steal data. The attack was publicly claimed by the group "Cutting Sword of Justice" shortly after the wiper was deployed.

Password Spray Campaign (Feb–Jul 2023)

Feb 2023 – Jul 2023 | United States | Defense | Pharmaceutical

Microsoft observed Peach Sandstorm conducting large-scale password spray campaigns against Azure AD tenants in the defense industrial base and pharmaceutical sectors. The group used a botnet of compromised IoT devices to distribute login attempts, making traditional IP-based blocking ineffective. Successful credentials were used to access Microsoft 365 mailboxes and exfiltrate email data. Microsoft published detailed guidance on detecting and mitigating the campaign, including recommendations for implementing multi-factor authentication and monitoring for anomalous sign-in patterns.

FalseFont Backdoor (Defense Industrial Base)

Active | Defense Industrial Base

Microsoft identified a new custom backdoor dubbed FalseFont targeting defense contractors in the defense industrial base sector. The backdoor was delivered via spearphishing emails with malicious Word documents exploiting CVE-2017-11882. FalseFont provides remote shell access, file upload/download, and keylogging capabilities, demonstrating APT33's continued investment in custom tooling.

Tickler Backdoor Campaign

Mar 2023 – Present | United States | UAE | Energy | Aviation

Between April and July 2023, Microsoft observed Peach Sandstorm deploying a new custom multi-stage backdoor named Tickler against targets in the aviation, communications equipment, oil and gas, and manufacturing sectors in the United States and the UAE. Tickler is capable of collecting system information, enumerating files, and executing additional payloads. Microsoft assessed with high confidence that Tickler is the successor to the TURNEDUP backdoor.

The group's C2 infrastructure relied on fraudulent Azure subscriptions, APT33-compromised education sector accounts, then created new Azure subscriptions to host redirectors and command-and-control servers. Microsoft noted that Peach Sandstorm actors used the C2 connection activity to locate RDP-exposed devices. Microsoft recommended defenders block the identified IP addresses and domains.

Microsoft Threat Intelligence, "Peach Sandstorm deploys new custom Tickler malware targeting the defense sector," December 2023.

Detection & Response Recommendations

Detection Opportunities

Cloud Authentication Anomalies
- Impossible travel alerts (sign-in sessions from distributed IP ranges) (T1078.004)
- Password spray patterns: single password tested against many accounts in sequence
- Service principal credential additions from unexpected IP addresses

Email Indicators
- Spearphishing emails with malicious Word documents (.docm) (T1566.001)
- New Azure subscription creation from recently compromised accounts
- Azure AD Security subscription creation from non-enterprise/organizational accounts

Tickler / FalseFont Indicators
- C2 HTTP beacon traffic with unusual User-Agent strings and periodic check-in intervals
- Base64-encoded PowerShell commands executed by scheduled tasks
- Files containing strings associated with Iranian-aligned threat actors in temporary directories

Post-Compromise Behaviors
- Azure Directory organization creation (Azure_DC.Exe)
- Azure Directory organization creation (Azure_DC.Exe)
- Azure Directory organization creation (Azure_DC.Exe)
- Azure Directory organization creation (Azure_DC.Exe)

Legacy Indicators (Operationalizing Exe)
- RDP connections from unusual geolocations or cloud infrastructure
- Kerberoasting (T1558.003) activity against service accounts with weak passwords
- Bulk email forwarding rules created in compromised mailboxes
- Shamoon-like MBR overwrite attempts (T1561.002)
- Stonedrill/DROPSHOT WMI event subscriptions on domain controllers
- Shamoon or RawDrv[.]Y Sysmon(Log) patterns

Sample Detection Queries

Password Spray Detection in Azure AD Sign-In Logs (KQL)

```
// Detect password spray patterns: many accounts, few passwords, distributed IPs
// Adjust thresholds based on your environment's baseline
let timeframe = 1h;
let min_failed_logins = 20;  // Tune: lower = more alerts, higher = fewer alerts
let min_accounts = 10;
SigninLogs
| where TimeGenerated > ago(timeframe)
| where ResultType != 0  // Failed sign-in attempts
| summarize FailedAttempts = count(), DistinctAccounts = dcount(UserPrincipalName), DistinctIPs = dcount(IPAddress), IPList = make_set(IPAddress, 10) by bin(TimeGenerated, 5m)
| where FailedAttempts >= min_failed_logins and DistinctAccounts >= min_accounts
| project TimeGenerated, FailedAttempts, DistinctAccounts, DistinctIPs, IPList
| order by TimeGenerated desc
```

Tickler Backdoor C2 Beacon Detection (Sigma)

```
title: Tickler Backdoor C2 Beacon Detection
id: 8f3a2c1d-4e5b-6f7a-8b9c-0d1e2f3a4b5c
status: experimental
description: Detects Tickler backdoor C2 beacon activity based on HTTP request patterns and User-Agent strings observed in APT33 campaigns
author: Intruvent Threat Intelligence
date: 2026/03/18
logsource:
  category: proxy
  product: any
detection:
  selection_uri:
    cs-uri-query|contains:
      - '/api/v1/update?id='
      - '/api/v1/config?id='
  selection_ua:
    cs-user-agent|contains:
      - 'Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36'
  filter_legitimate:
    cs-host|endswith:
      - '.microsoft.com'
      - '.windowsupdate.com'
  condition: selection_uri and selection_ua and not filter_legitimate
falsepositives:
  - Legitimate software update checks
level: high
tags:
  - attack.command_and_control
  - attack.t1071.001
  - attack.t1573.001
```

Azure Runbook Abuse Detection (KQL)

```
// Detect suspicious Azure Automation runbook creation or modification
// Attackers may create runbooks for persistence or lateral movement
AzureActivity
| where TimeGenerated > ago(24h)
| where OperationNameValue in~ (
    "MICROSOFT.AUTOMATION/AUTOMATIONACCOUNTS/RUNBOOKS/WRITE",
    "MICROSOFT.AUTOMATION/AUTOMATIONACCOUNTS/RUNBOOKS/DRAFT/WRITE",
    "MICROSOFT.AUTOMATION/AUTOMATIONACCOUNTS/RUNBOOKS/PUBLISH/ACTION"
)
| where ActivityStatusValue == "Success"
| project TimeGenerated, Caller, CallerIpAddress, ResourceGroup, Resource, OperationNameValue
| order by TimeGenerated desc
```

WMI Event Subscription Detection (KQL)

```
// Detect WMI event subscriptions commonly used for persistence
// Requires Sysmon Event ID 19, 20, 21 or Windows Event ID 5861
SecurityEvent
| where TimeGenerated > ago(24h)
| where EventID == 5861
| extract "Consumer = (.*?)\n", 1, Consumer
| extract "Filter = (.*?)\n", 1, Filter
| extract "Binding = (.*?)\n", 1, Binding
| project TimeGenerated, Computer, Consumer, Filter, Binding
| order by TimeGenerated desc
```

Sysmon Process Creation Rule

```
<!-- Sysmon configuration snippet for APT33 detection -->
<!-- Add to your Sysmon config under <EventFiltering> -->
<RuleGroup name="APT33 Detection" groupRelation="or">
  <ProcessCreate onmatch="include">
    <CommandLine condition="contains">-EncodedCommand</CommandLine>
    <CommandLine condition="contains">-enc</CommandLine>
    <CommandLine condition="contains">FromBase64String</CommandLine>
    <ParentImage condition="contains">\Temp\</ParentImage>
    <ParentImage condition="contains">\Users\Public\</ParentImage>
  </ProcessCreate>
</RuleGroup>
```

Tickler Beacon Detection (Splunk)

```
index=proxy sourcetype=web_proxy
| rex field=uri_query "id=(?<beacon_id>[a-f0-9]{32})"
| where isnotnull(beacon_id)
| stats count, dc(src_ip) as unique_sources, values(user_agent) as user_agents by beacon_id, dest_host
| where count > 10 and unique_sources < 3
| eval threat_actor="APT33", malware="Tickler"
| table beacon_id, dest_host, count, unique_sources, user_agents, threat_actor, malware
```

Shamoon Wiper Detection (Windows Event Log)

```
index=wineventlog EventCode=4688
| where match(CommandLine, "(?i)(shamoon|trksvr|netinit|drivers\.exe)")
| where match(CommandLine, "(?i)(\\\\.\\PhysicalDrive|\\\\.\\RawDisk)")
| table _time, ComputerName, User, CommandLine, ParentProcessName
| sort _time
```

Tickler Obfuscation Detection (YARA)

```
rule Tickler_Obfuscation_Detection {
    meta:
        description = "Detects Tickler backdoor with XOR-encoded strings"
        author = "Intruvent Threat Intelligence"
        date = "2026-03-18"
        reference = "Intruvent-TICKLER-2023"
    strings:
        $xor_key = { 4A 7F 2C 91 }  // Tickler's 4-byte XOR key
        $decode_loop = { 8A ?? ?? 30 ?? ?? 40 ?? ?? 3B ?? 75 ?? }
        $mz = "MZ"
    condition:
        $mz at 0 and $xor_key and $decode_loop
}
```

Mitigation Recommendations

- **Implement multi-factor authentication (MFA) on all cloud accounts.** MFA is the single most effective control against APT33's password spray campaigns. Prioritize Azure AD/Entra ID, Microsoft 365, and VPN access. (Source: Microsoft, April 2023)
- **Implement conditional access policies.** Block sign-ins from unexpected geographies, require compliant devices, and enforce risk-based authentication for high-value applications. (Source: Microsoft, April 2023)
- **Audit Azure subscription creation.** Alert on new subscriptions created by non-administrative users. Restrict subscription creation to approved administrators. (Source: Intruvent, based on observed attack patterns)
- **Monitor for anomalous RDP connections.** Alert on RDP connections from unusual geolocations or cloud infrastructure. (Source: Intruvent, based on observed attack patterns)
- **Deploy credential hygiene controls.** Enforce passwords for cloud-based authentication accounts. Implement password rotation policies for service accounts. (Source: Intruvent, based on observed attack patterns)
- **Review for suspicious OAuth app registrations.** Monitor for unusual refresh token activity and unexpected application permissions. (Source: Microsoft, April 2023)
- **Restrict subscription creation privileges.** If your organization includes educational accounts, limit their ability to create Azure subscriptions. (Source: Intruvent, based on observed attack patterns)

Appendix A: Indicators of Compromise

Working Evidence: C-Tier IOC Classification

The C-Tier IOC Classification

Intruvent's Threat Intelligence team uses a 7-dimension IOC classification framework, including Timeliness, Relevance, Accuracy, Specificity, Actionability, Context, and Confidence, to assess the quality of indicators.

The C-Tier IOC Classification: Operational Implications

C-Tier IOCs are characterized by their low specificity and high false positive rate. Because they are typically shared widely, they are commonly observed in benign environments. Their primary value is in broad, automated hunting and enrichment, rather than high-confidence alerting.

The C-Tier IOC Classification: Recommended Handling

- **Do not** block C-Tier IOCs at the perimeter without additional context. Their high false positive rate will cause significant disruption.
- **Do** use C-Tier IOCs to enrich alerts generated by higher-confidence indicators. For example, if a B-Tier IP is observed, check for C-Tier domains resolving to that IP.
- **Do** aggregate C-Tier IOCs over time to identify infrastructure clusters. Multiple C-Tier IOCs pointing to the same hosting provider may indicate a campaign.
- **Do** set a short expiration (TTL) for C-Tier IOCs in your threat intelligence platform. Stale indicators are more likely to cause false positives.

The C-Tier IOC Classification: Limitations

C-Tier IOCs may be useful for attribution in aggregate, but they are rarely sufficient on their own. Analysts should not make attribution decisions based solely on C-Tier indicators.

Tier 1: Analyst Environment

Tier 1 analysts have access to the following tools:

- Splunk Enterprise Security
- Microsoft Sentinel
- Microsoft Defender for Endpoint
- Microsoft Defender for Cloud
- Microsoft Defender for Identity
- Microsoft Defender for Office 365
- Microsoft Defender for Cloud Apps