SSRF Exploitation & Pre-Authenticated Access Detection

CVE-2026-5760 · SageMaker Model Deployment · Critical (9.8)

Table of Contents

Overview
Vulnerability Details
Affected Versions
Attack Surface
Exploitation Mechanics
Detection Strategy
Indicators of Compromise
Mitigation
Timeline
References

Overview

Vulnerability Summary

CVE ID	CVE-2026-5760
Vulnerability Type	Server-Side Request Forgery (SSRF)
Affected Service	Amazon SageMaker Model Deployment
Attack Vector	Network
Authentication Required	None
Impact	Unauthorized access to internal resources
Severity	Critical (9.8)

Executive Summary

A Server-Side Request Forgery (SSRF) vulnerability in Amazon SageMaker Model Deployment allows an unauthenticated attacker to send crafted HTTP requests to internal endpoints reachable from the model container. The vulnerability exists in the model invocation proxy layer, which fails to validate user-supplied URL parameters before forwarding requests.

Successful exploitation can expose instance metadata credentials, internal API responses, and data from other services within the VPC. Organizations running SageMaker endpoints with default network configurations are at elevated risk.

Timeline

Date	Event
2026-03-14	Vulnerability reported to AWS Security
2026-03-18	AWS confirms vulnerability
2026-03-25	Patch development begins
2026-04-02	Patch deployed to all regions
2026-04-03	CVE-2026-5760 published
2026-04-10	Public disclosure

Vulnerability Details

Root Cause

The SageMaker model invocation proxy accepts a `target_url` parameter in the request body and forwards the request to the specified endpoint. The proxy does not validate that the target URL resolves to an external address, allowing requests to internal IP ranges and the instance metadata service.

Affected Versions

Component	Affected Versions	Fixed Version
SageMaker Model Deployment	2.x < 2.241.0	2.241.0
SageMaker Inference Toolkit	1.x < 1.18.3	1.18.3
SageMaker Python SDK	2.x < 2.241.0	2.241.0
SageMaker Container Images	Pre-2026-04-02	2026-04-02

Attack Surface

Exploitation Mechanics

Prerequisites

- Network access to a SageMaker endpoint (public or VPC)
- Knowledge of the endpoint name
- No authentication credentials required

Attack Flow

1. Attacker identifies a SageMaker endpoint with a publicly accessible invocation URL
2. Attacker crafts a request with `target_url` pointing to `http://169.254.169.254/latest/meta-data/iam/security-credentials/`
3. The proxy forwards the request to the metadata service
4. The response containing IAM role credentials is returned to the attacker
5. Attacker uses the stolen credentials to access other AWS services

Proof of Concept

```
curl -X POST https://runtime.sagemaker.us-east-1.amazonaws.com/endpoints/my-endpoint/invocations \
  -H "Content-Type: application/json" \
  -d '{"target_url": "http://169.254.169.254/latest/meta-data/iam/security-credentials/"}'
```

> **Warning:** This PoC is provided for detection engineering purposes only. Do not use against systems you do not own or have explicit authorization to test.

Detection Strategy

Detection Logic

Monitor for SageMaker invocation requests where the request body contains URL patterns targeting internal IP ranges (169.254.0.0/16, 10.0.0.0/8, 172.16.0.0/12, 192.168.0.0/16) or the instance metadata service.

Log Sources

Log Source	Key Fields	Retention
SageMaker Endpoint Logs	`request_body`, `endpoint_name`, `source_ip`	30 days
VPC Flow Logs	`srcaddr`, `dstaddr`, `dstport`, `action`	90 days
CloudTrail	`eventName`, `sourceIPAddress`, `userAgent`	90 days
GuardDuty	`type`, `severity`, `resource`	90 days

Sigma Rule

```
title: SageMaker SSRF Exploitation Attempt
id: 8a3f2c1d-4e5b-6789-abcd-ef0123456789
status: experimental
description: Detects SSRF exploitation attempts against SageMaker endpoints
logsource:
  product: aws
  service: sagemaker
detection:
  selection:
    request_body|contains:
      - '169.254.169.254'
      - 'target_url'
  condition: selection
level: critical
```

Splunk Query

```
index=sagemaker sourcetype="aws:sagemaker:endpoint"
| search request_body="*169.254.169.254*" OR request_body="*target_url*"
| table _time, endpoint_name, source_ip, request_body
```

Elastic Query

```
event.dataset: "aws.sagemaker" AND
(request_body: *169.254.169.254* OR request_body: *target_url*)
```

Datadog Query

```
source:aws.sagemaker @request_body:(*169.254.169.254* OR *target_url*)
```

Microsoft Sentinel Query

```
AWSCloudTrail
| where EventSource == "sagemaker.amazonaws.com"
| where RequestParameters has "169.254.169.254" or RequestParameters has "target_url"
| project TimeGenerated, SourceIpAddress, UserIdentityArn, RequestParameters
```

Chronicle Query

```
metadata.product_name = "Amazon SageMaker"
request_body = /169\.254\.169\.254|target_url/
```

Google SecOps Query

```
metadata.product_name = "Amazon SageMaker"
request_body = /169\.254\.169\.254|target_url/
```

Exabeam Query

```
index=sagemaker sourcetype="aws:sagemaker:endpoint"
| search request_body="*169.254.169.254*" OR request_body="*target_url*"
| table _time, endpoint_name, source_ip, request_body
```

Cortex XDR Query

```
dataset = aws_sagemaker_endpoint
| filter request_body contains "169.254.169.254" or request_body contains "target_url"
| fields _time, endpoint_name, source_ip, request_body
```

SentinelOne Query

```
event.type = "SageMaker Endpoint Invocation"
AND (request_body contains "169.254.169.254" OR request_body contains "target_url")
```

Anomaly Detection

Establish a baseline of normal invocation patterns per endpoint. Alert on:

- Requests containing URL parameters in the request body
- Requests from unexpected source IPs
- Spikes in invocation volume from a single source
- Requests to endpoints that have not been invoked in the past 30 days

Indicators of Compromise

Network Indicators

Indicator	Type	Description
169.254.169.254	IP	Instance metadata service
fd00:ec2::254	IP	IMDSv2 IPv6 endpoint
10.0.0.0/8	CIDR	Internal VPC range
172.16.0.0/12	CIDR	Internal VPC range
192.168.0.0/16	CIDR	Internal VPC range

Host Indicators

Indicator	Type	Description
`/latest/meta-data/iam/security-credentials/`	Path	IAM credential retrieval
`/latest/user-data`	Path	Instance user data retrieval
`/latest/dynamic/instance-identity/document`	Path	Instance identity document

Behavioral Indicators

- Unusual outbound connections from SageMaker container to non-standard ports
- DNS queries for internal hostnames from model containers
- Credential usage from unexpected geographic locations
- Rapid sequential requests to multiple endpoints from the same source

Mitigation

Patch Information

Update to the following versions or later:

- SageMaker Model Deployment: 2.241.0
- SageMaker Inference Toolkit: 1.18.3
- SageMaker Python SDK: 2.241.0
- SageMaker Container Images: 2026-04-02

Workarounds

If patching is not immediately possible:

1. Enable network isolation on SageMaker endpoints
2. Configure VPC endpoints for AWS services
3. Use IMDSv2 with hop limit set to 1
4. Implement egress filtering on container network interfaces

Configuration Changes

```
{
  "EnableNetworkIsolation": true,
  "VpcConfig": {
    "SecurityGroupIds": ["sg-0123456789abcdef0"],
    "Subnets": ["subnet-0123456789abcdef0"]
  }
}
```

Network Segmentation

Place SageMaker endpoints in dedicated subnets with restrictive security groups. Block outbound traffic to link-local addresses (169.254.0.0/16) at the network level.

Access Control

Restrict `sagemaker:InvokeEndpoint` permissions to specific IAM roles and principals. Use resource-based policies to limit which VPCs can reach the endpoint.

References

- AWS Security Bulletin: CVE-2026-5760
- SageMaker Model Deployment Release Notes
- Instance Metadata Service Version 2 (IMDSv2) Documentation
- SageMaker Network Isolation Configuration Guide
- Server-Side Request Forgery Prevention Cheat Sheet